


# Instrument Processing



We believe design is about more than the space or technology being used.



As antimicrobial resistance and the emergence of novel viral pathogens loom larger in headlines, the need for infection control across health systems has reached a new urgency. Keeping patients and staff safe is at the heart of any effective infection control measure, so a better understanding of and adherence to instrument processing best practices is truly essential for every facility.




# Infection Prevention Matters

Every day patients walk into healthcare facilities to be treated and walk out with a healthcare acquired infection (HAI). These types of infections can have devastating medical and financial implications—worse, they can be deadly.<sup>1</sup> And HAIs are not limited to hospitals. Don't take chances with the health of your patients and staff, or the safety standards of your health system.

Midmark instrument processing solutions provide the solid foundation you need for worry-free infection prevention measures, based on best practices you can trust.

**2 MILLION**  
PEOPLE DEVELOP AN HAI  
EACH YEAR IN THE US.<sup>2</sup>



# Instrument Processing Essentials

Follow the instrument processing best practices established by the CDC<sup>3</sup> to create a smooth workflow from dirty to clean, helping contain contamination and maximizing the efficiency of your instrument cleaning and sterilization processes.



## STEP 1

### Receiving, Cleaning + Decontamination

Reusable instruments, supplies and equipment should be received, cleaned and decontaminated in one section of the processing area.

## STEP 2

### Preparation + Packaging

Cleaned instruments and other supplies should be inspected, assembled into sets or trays, and wrapped or packaged for sterilization.

## STEP 3

### Sterilization

The sterilization area should include the sterilizer and related supplies with adequate space for loading, unloading and cool down.

## STEP 4

### Monitoring/Sterility Assurance

Use and keep record of mechanical, chemical and biological monitoring to ensure the effectiveness of the sterilization process.

## STEP 5

### Storage

The storage area should contain space for sterile items and disposables. Supplies and instruments should not be stored under sinks or in other locations where they might become wet.

# The Critical First Step QuickClean® Ultrasonic Cleaners

If an instrument is not clean, it will not become sterile. That's why it's so important to ensure that instruments are thoroughly cleaned prior to sterilization. QuickClean Ultrasonic Cleaners can eliminate hidden residues manual cleaning may miss, providing powerful, effective cleaning with consistent results. And QuickClean uses advanced technology to help create a safer, more efficient work environment by decreasing worker exposure to contaminants and sharps injuries while reducing the time and effort needed for cleaning.



01



02



03

**01** Choose the option that best fits your space and workflow needs. QuickClean comes in three tabletop sizes (1.2-, 3.3- and 6.6-gallon).

**02** QuickClean is available in two recessed options (3.3- or 6.6-gallon).

**03** The stainless steel finish and attractive design coordinate well with most décor.

# Simple, Powerful Technology

QuickClean® is easy to use right out of the box, so your staff can be up and running with minimal training time. Advanced Frequency-Leap technology helps ensure your instruments are fully cleaned the first time, every time no matter where they are placed in the basket.



## ACCESSORIES + SERVICE PARTS



### Beaker Accessories

- 9A612001 - QC1 – 2 Beaker Accessory
- 9A613001 - QC3/QC3R – 4 Beaker Accessory
- 9A614001 - QC6/QC6R – 6 Beaker Accessory



### Extra Safety Baskets

- 002-10007-00 - QC1 Safety Basket
- 002-10008-00 - QC3/QC3R Safety Basket
- 002-10009-00 - QC6/QC6R Safety Basket



### Cleaning Solutions

- 9A296001 Midmark General Purpose Cleaner (32 oz)
- 9A297001 Midmark Tartar and Stain Remover (32 oz)
- 9A298001 Midmark Enzymatic Cleaner (32 oz)

## QUICKCLEAN MODELS

	QC1-01	QC3-01	QC3R-01	QC6-01	QC6R-01
Type of Unit	Tabletop Unit	Tabletop Unit	Recessed Unit	Tabletop Unit	Recessed Unit
Capacity	1.2 Gal/4.5 L	3.3 Gal/12.5 L	3.3 Gal/12.5 L	6.6 Gal/25 L	6.6 Gal/25 L
Size of Unit	13.5" L x 10.2" W x 10.4" H (34.5 x 20 x 26.5 cm)	14.7" L x 16.5" W x 10.4" H (37.5 x 42 x 26.5 cm)	15.55" L x 14.37" W (39.5 x 36.5 cm)	21.6" L x 16.5" W x 14.3" H (55 x 42 x 36.5 cm)	22.48" L x 14.37" W (57.1 x 36.5 cm)
Size of Tank	11.8" L x 5.9" W x 5.9" H (30 x 15 x 15 cm)	13" L x 11.8" W x 5.9" H (33 x 30 x 15 cm)	13" L x 11.8" W x 5.9" H (33 x 30 x 15 cm)	19.9" L x 11.8" W x 7.9" H (50.5 x 30 x 20 cm)	19.9" L x 11.8" W x 7.9" H (50.5 x 30 x 20 cm)
Limited Warranty	3 Years	3 Years	3 Years	3 Years	3 Years
Average Sound Level (with lid on)	68 dB	61 dB	61 dB	69 dB	66 dB

# Trust the Best

## RITTER® M9 + M11 STEAM STERILIZERS

When you invest in Ritter sterilizers, you can be confident you are getting the best—our sterilizers are the market leaders year after year. Ritter sterilizers are designed to be safe, dependable and easy to use. In fact, every unit is inspected by an ASME third-party licensed inspector. And all our sterilizers are backed with over 100 years of manufacturing experience built into each one.

---

### SAFETY FEATURES

**Programmed Controls:** Once a pre-programmed cycle is selected, the unit is designed to sterilize automatically without any operator assistance.

**Smart Technology:** If the door isn't closed completely or the water level is low, the sterilizer will automatically stop and alert the operator to take proper action.

**Open-Door Drying:** Once sterilization is complete, the door opens automatically and quietly to dissipate steam and dry your instruments.



#### 01 Ritter M11® Steam Sterilizer

Its 11" x 18" chamber makes it the largest of any standard countertop sterilizer on the market.

#### 02 Ritter M9® Steam Sterilizer

Pack all the reliable sterilizing power you need into a compact unit perfect for areas with limited space.

# ACCESSORIES THAT HELP ADD VERSATILITY + FUNCTION



## STANDARD CYCLE PARAMETERS

Pre-Programmed Cycle	Sterilization Temperature	Hot Cycle Time (Fill, Heat-Up + Vent in minutes)		Sterilization Time (in minutes)		Dry Time (in minutes)		Total Hot Cycle Time w/o Dry (in minutes)		Total Hot Cycle Time w/ Dry (in minutes)	
		M11	M9	M11	M9	M11	M9	M11	M9	M11	M9
Unwrapped	270°F (132°C)	19	11	3	3	30	30	22	14	52	44
Pouches	270°F (132°C)	20	12	4	4	30	30	24	16	54	46
Packs/Low Temp	250°F (121°C)	18	10	30	30	30	30	48	40	78	70
Handpieces	270°F (132°C)	26	15	4	4	30	30	30	19	60	49

## ACCESSORIES FOR THE M9® + M11® STERILIZERS



**M9/M11 Printer 9A599001**  
Records and prints critical sterilization cycle data including time, temperature and pressure.



**Cool Hand Tool 9A307001**  
Designed to help reduce the risk of staff injury by making it safer and simpler to load and unload your sterilizer.



**Pouch Rack 002-2108-00 + 002-2108-01**  
Designed to separate sterilization pouches for enhanced steam circulation and drying.




**Sterilizer Data Logger 9A682001**  
Simplify and streamline the documentation of physical and mechanical performance (sterilization time and temperature) of every sterilization cycle.



**Data Logger USB Device 002-10502-00**  
Replacement or additional USB devices are available for the Sterilizer Data Logger.

## VISTACOOL™ DIRECT-TO-DRAIN WATER ELIMINATION SYSTEM



**Double VistaCool unit 9A586002**  
Designed to be compatible with any two current Ritter® sterilizers

The VistaCool Direct-To-Drain sterilizer wastewater elimination system makes labor-intensive condensate tanks unnecessary, freeing your staff to spend more time with patients and less time tending to equipment.



# Your Instrument Processing Center

## **STERILIZATION GOALS MAY BE UNIVERSAL, BUT EACH FACILITY IS UNIQUE.**

Even though you may be familiar with sterilization and instrument processing best practices, the needs and considerations of each facility can be different. These variations can make implementing a sterilization and instrument processing workflow that adheres to best practices a challenge.

Let us help you create an instrument processing center that addresses the specific needs of your facility, your team and your patients. We can help standardize your instrument processing workflow in one facility or across a network of sites.



# Configure Your Space

From receiving to storage, your instrument processing space needs to work for you. These layout options are designed to follow the 5-step best practices in instrument processing while giving you the options your practice demands.


**STEP 1**  
RECEIVING, CLEANING  
+ DECONTAMINATION

**STEP 2**  
PREPARATION + PACKAGING

**STEP 3**  
STERILIZATION


**STEP 4**  
MONITORING/STERILITY  
ASSURANCE

**STEP 5**  
STORAGE




## GALLEY

The galley layout consists of workspaces on two opposing walls with a single traffic lane between. This arrangement allows for easy access and efficient workflow, helping your staff keep the process moving using a linear flow while also keeping everything within reach.




## L-SHAPED

An L-shaped counter arrangement maximizes use of available space where elbow room is limited. The space you have can be all you need for a better instrument processing workflow.



## U-SHAPED

Multiple cleaners and sterilizers demand space—a U-shaped workspace design provides that and more. Ample surface areas allow more staff in the room to multitask and maintain a bustling workflow.



## STRAIGHT LINE

Perfectly suited to the 5-step instrument processing flow, a straight-line workspace design is the picture of efficiency.

# Synthesis® Color + Style Options

Synthesis Cabinetry offers different color and styling options to allow you to put your unique signature on a space, whether it is in one office or a multi-facility organization.


## HANDLE STYLES



## PANEL STYLES



## CABINET FINISH



\*EPA registration number 85353-2  
\*\*Available in Pebble Grey or Pebble Grey PVC Free only

# Midmark® Cabinetry vs. Local Millwork

Why Midmark? We can think of many reasons—and it all starts with a better design. The Synthesis cabinetry line is carefully designed and constructed with the clinical space in mind. We incorporate the functional features you will come to appreciate, such as full-extension drawers and asepsis-friendly surfaces that are easy to clean and maintain. We understand wanting to support the shop down the road, but local millwork alternatives are unlikely to match Midmark cabinetry solutions for quality, durability and design.

## CABINET FRAME



- 01 Synthesis Cabinetry**
- 18-gauge cold-rolled steel
  - Modular design
- 02 Local Millwork**
- Often made from 1/2" to 5/8" low-density particle board or various types of plywood
  - Basic or limited designs

## PANEL SUBSTRATES




- 01 Synthesis Cabinetry**
- Medium-density fiberboard
  - 3/4" panels
- 02 Local Millwork**
- Low-density particle board
  - Various types of plywood

## TYPES OF ASSEMBLY




- 01 Synthesis Cabinetry**
- Mechanical fasteners (screws, pop rivets) and Tog-L-Loc® sheet metal joining system
- 02 Local Millwork**
- Frequently use staple fasteners

## DRAWERS




- 01 Synthesis Cabinetry**
- Seamless, polystyrene drawers
- 02 Local Millwork**
- Inside drawers are often varnished, painted or left unfinished

## BASE MATERIAL



- 01 Synthesis Cabinetry**
- Thermofoil over electrostatic, powder-coated painted steel (woodgrain and metallic colors)
  - Electrostatic, powder-coated painted steel (solid colors)
  - Integrated adjustable levelers
- 02 Local Millwork**
- Basic plywood or particle board covered with laminate
  - Wood shims used for leveling

## FINISHES




- 01 Synthesis Cabinetry**
- PVC thermofoil (woodgrain and metallic colors)
  - PVC thermofoil and electrostatic, powder-coated paint (solid colors)
- 02 Local Millwork**
- High-pressure laminate
    - Do not always follow proper application methods
    - May use low-grade substrate material
    - Less than 2 mm edgebanding
  - Varnished, painted or left unfinished

## DRAWER SLIDES



- 01 Synthesis Cabinetry**
- Full extension ball bearing drawer system
  - Secured to steel foundation
- 02 Local Millwork**
- Typically use a single, undermounted runner (monorail glide) or slides common in kitchens (less durable)

## HANDLES



- 01 Synthesis Cabinetry**
- Integrated and insert handle option
  - Brushed nickel pull options
  - Antimicrobial option
- 02 Local Millwork**
- Most use "C" style pulls made of plastic or aluminum

Fabrication of local cabinets may vary. However, materials depicted are typical of local millwork cabinetry.



# What You Get With Midmark



## PROVEN DESIGNS

Midmark instrument processing solutions are designed from the inside out to perform consistently throughout the life of the product. Our products do their job, so you can do yours.



## EFFECTIVE TECHNOLOGY

What good is technology if it's not easy to use? Midmark instrument processing solutions are built to be simple to use right out of the box. And if you ever need help, we're here.



## RELIABLE SUPPORT

You may not think about your instrument processing equipment until it goes down. But rest assured that if it does, we'll be there to get you back up and running quickly.

---

## DESIGN SUPPORT

Whether you are building a new practice or remodeling your current instrument processing center, the prospect can be overwhelming. Our in-house design experts are ready to help you every step of the way, including partnering with your preferred dealer and working with existing floorplans and designs. We can help you choose from a variety of designs, configurations and styles and all specific to your instrument processing needs. Let's design a better instrument processing experience.



# SPECIFICATIONS

## M11®

Length w/plug: 23.8" (60.5 cm)  
Width: 17.8" (45.2 cm)  
Height w/printer: 17.8" (45.2 cm)

Minimum Countertop Area:  
17.8" W x 21" D (45.2 x 53.3 cm)

Chamber: 11" x 18" (28 x 45.7 cm)  
6.5 gal usable volume (24.6 L)

Trays:  
Two Large – 9" W x 15" L x 1.1" D  
(22.9 x 38 x 2.9 cm)

Two Small – 6.6" W x 15" L x 1.1" D  
(16.8 x 38 x 2.9 cm)

Pouch Rack: 6 slot

Unit Weight: 99 lb (44.9 kg)  
Shipping Weight: 131 lb (59.4 kg)  
Water Reservoir Capacity: 1.4 gal (5.3 L)

## M9®

Length w/plug: 20.4" (51.8 cm)  
Width: 15.3" (38.9 cm)  
Height w/printer: 15.8" (40.1 cm)

Minimum Countertop Area:  
15.3" W x 17.9" D (38.9 x 45.4 cm)

Chamber: 9" x 15" (22.9 x 38.1 cm)  
3.5 gal usable volume (4.1 L)

Trays:  
Two Large - 7.3" W x 12" L x 0.8" D  
(18.6 x 30.5 x 2.2 cm)

Two Small - 5.6" W x 12" L x 0.8" D  
(14.3 x 30.5 x 2.2 cm)

Pouch Rack: 5 slot

Unit Weight: 73 lb (33.2 kg)  
Shipping Weight: 81 lb (36.7 kg)  
Water Reservoir Capacity: 1.1 gal (4.1 L)

## M9 + M11 ELECTRICAL REQUIREMENTS

115 VAC, 50/60 Hz, 15 A Single Phase  
115 VAC has 1,425 W tubular immersion heater

## ALL RITTER® STERILIZERS

Meet the requirements of ASME Boiler and Pressure Vessel Code Canadian Registered – CRN number is available  
Recommend a separate (dedicated) circuit  
1 Year Limited Warranty

## QC1 ULTRASONIC CLEANER

Tank Capacity 1.2 gal (4.5 L)  
Length: 13.5" (34.5 cm)  
Width w/drain: 10.2" (26 cm)  
Height: 10.4" (26.5 cm)  
Tank Size: 11.8" L x 5.9" W x 5.9" H (30 x 15 x 15 cm)  
Tabletop Unit Weight: 12.7 lb (5.76 kg)  
Tabletop Shipping Weight: 14.6 lb (6.64 kg)

## QC1 ELECTRICAL REQUIREMENTS

Input: 115 VAC +/-10%, 60 Hz, 110 W, 1.0 A  
Output: 100 W

## QC3/QC3R ULTRASONIC CLEANER

Tank Capacity: 3.3 gal (12.5 L)  
Length: 14.7" (37.5 cm)  
Width w/drain: 16.5" (42 cm)  
Height: 10.4" (26.5)  
Tank Size: 13" L x 11.8" W x 5.9" H (33 x 30 x 15 cm)  
Tabletop Unit Weight: 18.6 lb (8.42)  
Tabletop Shipping Weight: 20.9 lb (9.5 kg)  
Recessed Unit Weight: 22.3 lb (10.10 kg)  
Recessed Unit Shipping Weight: 24.6 lb (11.18 kg)

## QC3/QC3R ELECTRICAL REQUIREMENTS

Input: 115 VAC +/- 10%, 60 Hz, 210 W, 1.8 A  
Output: 200 W

## QC6/QC6R ULTRASONIC CLEANER

Tank Capacity: 6.6 gal (25L)  
Length: 21.6" (55 cm)  
Width w/drain: 16.5" (42 cm)  
Height: 14.3" (36.5 cm)  
Tank Size: 19.8" x 11.8" x 7.8" (50.5 x 30 x 20 cm)  
Tabletop Unit Weight: 29.6 lb (13.44 kg)  
Tabletop Shipping Weight: 32.6 lb (14.78 kg)  
Recessed Unit Weight: 32.9 lb (14.92 kg)  
Recessed Unit Shipping Weight: 35.8 lb (16.26 kg)

## QC6/QC6R ELECTRICAL REQUIREMENTS

Input: 115 VAC +/- 10%, 60 Hz, 410 W, 3.6 A  
Output: 400 W

## M9/M11 ACCESSORIES + SUPPLIES:

9A599001 Thermal Printer  
002-2108-00 6 Slot Pouch Rack  
002-2108-01 5 Slot Pouch Rack  
9A307001 Cool Hand Tool  
002-0396-00 Speed-Clean, 1 (16 oz/0.47 L) bottle  
002-0396-05 Speed-Clean Case – 12 bottles  
9A586002 Double VistaCool Unit  
9A682001 Sterilizer Data Logger  
002-10502-00 Data Logger USB Device

## QUICKCLEAN ACCESSORIES + SUPPLIES

9A612001 QC1 - 2 Beaker Accessory  
9A613001 QC3/QC3R - 4 Beaker Accessory  
9A614001 QC6/QC6R - 6 Beaker Accessory  
9A296001 Midmark General Purpose Cleaner (32 oz)  
9A298001 Midmark Enzymatic Cleaner (32 oz)  
9A297001 Midmark Tartar and Stain Remover (32 oz)  
002-10007-00 QC1 Safety Basket  
002-10008-00 QC3/QC3R Safety Basket  
002-10009-00 QC6/QC6R Safety Basket

# SOURCES

1 <https://www.cdc.gov/hai/patientsafety/patient-safety.html>

2 <https://journals.sagepub.com/doi/10.1177/003335490712200205>

3 <https://www.cdc.gov/infectioncontrol/guidelines/disinfection/sterilization/sterilizing-practices.html>



Designing better care.®



CARB 93129.2 Phase 2 Compliant and TSCA Title IV Compliant

Midmark is an ISO 13485 and ISO 9001 Certified Company. Certain products are not included. See the complete list at: [midmark.com/ISO](http://midmark.com/ISO)

For more information, contact your Midmark dealer or call: 1.800.MIDMARK  
Outside the USA call: 1.937.526.3662 or visit our website: [midmark.com](http://midmark.com)

VistaCool™ Direct-to-Drain System for Autoclave Wastewater is manufactured by Crosstex International, Inc., for distribution by Midmark Corporation, Versailles, OH.

VistaCool™ is a trademark of Crosstex International, Inc., a Cantel Medical Company, Hauppauge, NY.

Tog-L-Loc is a registered trademark of BTM Corporation, Bloomfield Hills, MI.

© 2021 Midmark Corporation, Miamisburg, Ohio USA  
Products subject to improvement changes without notice. Litho in USA.

007-10191-00 Rev. C1 (12/21)

